



# FUYR BEARING CO.,LTD.



## QM INDUSTRIES QVFXP16V070SM Flange Block Bearings

Bearing No. QVFXP16V070SM

QVFXP16V070SM Bearing 2D drawings and 3D CAD models

|                           |  |
|---------------------------|--|
| Category                  | Flange Block Bearings  |
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 7.718  |
| EAN                       | 0883450978835  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | V Lock   |
| Housing Style             | 4 Bolt Square Flange Block   |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 20 Millimeter  |
| Relubricatable            | Yes  |
| Insert Part Number        | 22216  |
| Seals                     | Triple Lip Nitrile Rubber  |
| Housing Configuration     | 1 Piece Solid  |
| Pilot Configuration       | With Pilot   |
| Inch - Metric             | Metric   |
| Long Description          | 4 Bolt Square Flange Block; 70MM Bore; 215MM Bolt Circle; 152.7MM Bolt Spacing; 1 Piece Solid; V Lock Mount; Cast Steel; Spherical Roller Bearing; 83.6MM Length Thru Bore; Relubricatable; Triple Lip N |



## FUYR BEARING CO.,LTD.

|                                    |   |
|------------------------------------|---|
| Other Features                     | Double Row   Single Nut   |
| Category                           | Flange Block  |
| UNSPSC                             | 31171501  |
| Harmonized Tariff Code             | 8483.20.40.80   |
| Noun                               | Bearing   |
| Keyword String                     | Flanged   |
| Manufacturer URL                   | <a href="http://www.qmbearings.com">http://www.qmbearings.com</a> |
| Manufacturer Item Number           | QVFXP16V070SM   |
| Weight / LBS                       | 23  |
| d                                  | 2.756 Inch   70 Millimeter  |
| Bolt Spacing                       | 6.012 Inch   152.7 Millimeter                                     |
| D                                  | 3.291 Inch   83.6 Millimeter                                      |
| Nominal Bolt Circle Diameter Round | 8.5 Inch   215 Millimeter   |
| Cartridge Pilot Diameter           | 6.313 Inch   160.35 Millimeter                                    |
| Cartridge Pilot Depth              | 0.188 Inch   4.775 Millimeter                                     |